

Limitations

Must be protected from damage during construction. Do not apply to wet surfaces. Avoid freezing. **Air-Bloc 33** shall not be applied when ambient (air) and substrate temperatures are below 40°F. The product should not be applied if it is raining, or if the possibility of rain is likely within 16 hours. The product should not be applied if it is expected that the ambient temperature will fall below 32°F within 48 hours.

Surface Preparation

All surfaces must be sound, dry, clean and free of oil, grease, dirt, excess mortar or other contaminants. New concrete should be cured for a minimum of 16 hours before **Air-Bloc 33** is applied. Concrete surfaces should be free of large voids and spalled areas.

Joint & Crack Treatment

Joints between panels of exterior grade gypsum, plywood and rigid insulation up to ¼" wide shall be filled with a trowel application of **Air-Bloc 33** and reinforced with a strip of 2" wide glass fiber tape prior to application of liquid membrane. Alternatively, joints may be sealed with a strip of **Blueskin® Breather, MetalClad or Foilskin®** membrane applied to the substrate. Joints between panels of exterior grade gypsum or plywood wider than ¼" must be sealed with **Blueskin® Breather, MetalClad or Foilskin®** membrane adhered to the primed substrate.

Cracks in masonry and concrete up to 1/4" wide shall be filled with a trowel application of **Air-Bloc 33** and reinforced with a strip of 2" wide glass fiber tape and allowed to cure overnight prior to application of the liquid membrane to the surface. Alternatively, the cracks may be sealed with a strip of **Blueskin® Breather, MetalClad or Foilskin®** membrane applied to the primed substrate. Cracks wider than 1/4" must be sealed with **Blueskin® Breather, MetalClad or Foilskin®** membrane adhered to the primed substrate lapped a minimum of 3" on both sides of the crack.

Surfaces should be tied in with beams, columns, window and door frames, etc., using strips of **Blueskin® Breather, MetalClad or Foilskin®** lapped to primed substrate a minimum of 3" beyond transition joint. Mechanical attachment should be made to all window and doorframes or a properly designed sealant joint provided.

Surfaces to receive **Blueskin® Breather** membrane must be primed with or **Aquatac™ primer**. Surfaces to receive **Foilskin® or MetalClad** membranes should be primed with **Blueskin® primer, SprayPrep or Aquatac™ primer**. Refer to specific data sheet for application and rate of coverage of primer.

Application

Air-Bloc 33 may be applied by brush, however application by conventional air spray is the preferred method. The material should be applied at a rate of 6 gal / 100ft² (100 mils nominal). **Air-Bloc 33** can be applied in a single coat. The preferred method of application is to mark areas off and ensure that the appropriate volume has been sprayed over this area. During spraying, the material should be applied in horizontal strokes ensuring even application of the product, and then applied in vertical strokes, again ensuring even application.

Where **Blueskin® Breather** is used, **Air-Bloc 33** should be fully applied over the **Blueskin® Breather** to protect the membrane from UV exposure.

Clean Up

Use waterless hand cleaner for skin. Spray equipment can be flushed out with water. Use citrus based cleaners to remove dried films.

Caution

DO NOT TAKE INTERNALLY! Use protective measures to avoid contact with eyes and skin. If swallowed, **CALL PHYSICIAN IMMEDIATELY!** In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **GET MEDICAL ATTENTION!** Do not heat container or store at temperatures greater than 120°F. Close container after each use. **KEEP OUT OF REACH OF CHILDREN.**

Limited Warranty

We, the manufacturer, warranty only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES:** The Limited Warranty is IN LIEU OF any other warranties express or implied including but not limited to any implied warranty of MERCHANTABILITY or fitness for a particular purpose, and we, the manufacturer, shall have no further liability of any kind including liability for consequential or incidental damages resulting from any defects or any delays caused by replacement or otherwise. <>