



MATERIAL SAFETY DATA SHEET

Page 1 of 6

HE280DC - WHITE ELASTOMERIC ROOF COATING

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 11/09/2009 Product Name: HE280DC - WHITE ELASTOMERIC ROOF COATING Product Code: HE280DC	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
acrylic polymer blend	not avail.		15 - 40
aluminum hydroxide	21645-51-2		7 - 13
calcium carbonate	1317-65-3		7 - 13
silica, quartz	14808-60-7		0.1 - 1
titanium dioxide	13463-67-7		5 - 10
water	7732-18-5		25 - 50
zinc oxide (as zinc)	1314-13-2		3 - 7
inert ingredients			<Balance>

EMERGENCY OVERVIEW	
CAUTION! Direct skin and eye contact may cause irritation. Ingestion may cause gastric distress. Inhalation may cause irritation to the respiratory tract.	
Appearance/Odor: Creamy, white liquid, paint-like odor	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).
Skin Hazards None expected, however, prolonged contact may cause irritation.



HE280DC - WHITE ELASTOMERIC ROOF COATING

<p>3. Hazards Identification - Continued</p> <p><u>Ingestion Hazards</u> May cause liver and kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.</p> <p><u>Inhalation Hazards</u> None expected, however, certain individuals may experience minor nausea or headaches.</p> <p><u>Chronic/Carcinogenicity Effects</u> This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.</p>
<p>4. First Aid Measures</p> <p><u>Eye</u> In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.</p> <p><u>Skin</u> Remove contaminated clothing and shoes. Wash affected areas with soap and water.</p> <p><u>Ingestion</u> Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.</p> <p><u>Inhalation</u> Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Contact a physician if symptoms develop.</p>
<p>5. Fire Fighting Measures</p> <p>Flash Point: >212 °F Flash Point Method: Setaflash Lower Explosive Limit: not available Upper Explosive Limit: not available</p> <p><u>Fire And Explosion Hazards</u> Product is not considered flammable or combustible. Products of combustion include compounds of carbon, hydrogen, oxygen, aluminium and zinc, including carbon monoxide.</p> <p><u>Extinguishing Media</u> Carbon dioxide, water, water fog, dry chemical, chemical foam.</p> <p><u>Fire Fighting Instructions</u> Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Firefighters should wear self-contained breathing apparatus and full protective gear.</p>
<p>6. Accidental Release Measures</p> <p>Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations.</p>
<p>7. Handling And Storage</p> <p><u>Handling And Storage Precautions</u> Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Protect from physical damage. Protect from extreme temperatures. Keep out of reach of children.</p>



HE280DC - WHITE ELASTOMERIC ROOF COATING

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator. Respirator use may be required due to secondary operations such as mixing, spraying, sanding, buffing, etc.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

aluminum hydroxide

- ACGIH TLV-TWA: 10 mg/m3 (as aluminum metal)
- OSHA PEL-TWA: 15 mg/m3 (as aluminum metal) (total dust)
- OSHA PEL-TWA: 5 mg/m3 (as aluminum metal) (respirable dust)

calcium carbonate

- OSHA PEL-TWA 15 mg/m3 (total dust)
- OSHA PEL-TWA 5 mg/m3 (respirable dust)

silica, quartz

- ACGIH TLV-TWA 0.025 mg/m3
- OSHA PEL-TWA 30mg/m3 / (%SiO₂+2) (total dust)
- OSHA PEL-TWA 10 mg/m3/ (%SiO₂+2) (respirable dust)

titanium dioxide

- ACGIH TLV-TWA 10 mg/m3 (respirable)
- OSHA PEL-TWA 15 mg/m3 (total dust)

zinc oxide (as zinc)

- ACGIH TLV-STEL 10 mg/m3
- ACGIH TLV-TWA 2 mg/m3
- OSHA PEL-TWA 5 mg/m3
- OSHA PEL-TWA 15 mg/m3

9. Physical And Chemical Properties

Appearance

Creamy, white liquid

Odor

Paint-like odor

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 212 °F

Specific Gravity: 1.34



HE280DC - WHITE ELASTOMERIC ROOF COATING

9. Physical And Chemical Properties - Continued
Odor - Continued Vapor Pressure: 760@ 212°F Vapor Density: >1 pH Factor: >9.0 Solubility: dispersible Evaporation Rate: <1
10. Stability And Reactivity
Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) Extreme temperatures Incompatible Materials Strong oxidizers, strong acids Hazardous Decomposition Products Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, aluminum and zinc fumes and smoke may be produced. Conditions To Avoid (Polymerization) none
11. Toxicological Information
Chronic/Carcinogenicity IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans (Group 2B): titanium dioxide ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist. Miscellaneous Toxicological Information Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below. Ingredient(s) - Toxicological Data calcium carbonate oral-rat LD50: 6450 mg/kg silica, quartz iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um) zinc oxide (as zinc) Oral-mouse LD50: 7950 mg/kg Inhal-mouse LC50: 2500 mg/m3
12. Ecological Information
Ecotoxicological Information Data not available for this mixture. Acute Toxicity - Fish And Invertebrates Titanium dioxide:



HE280DC - WHITE ELASTOMERIC ROOF COATING

12. Ecological Information - Continued

Acute Toxicity - Fish And Invertebrates - Continued

96-hour LC50, fathead minnows: >1000 mg/L

Toxicity - Aquatic And Terrestrial Plants

Data not available for this mixture or the components within.

Acute And Dietary Toxicity - Birds

Data not available for this mixture or the components within.

Toxicity - Beneficial Microorganisms

Data not available for this mixture or the components within.

Environmental Fate Information

Data not available for this mixture or the components within.

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground Not Restricted

IMDG Not Restricted

IATA Not Restricted

15. Regulatory Information

SARA Hazard Classes

Acute Health Hazard

Ingredient(s) - U.S. Regulatory Information

zinc oxide (as zinc)

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

Ingredient(s) - State Regulations

calcium carbonate

Pennsylvania - Workplace Hazard

silica, quartz

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

titanium dioxide

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

New York City - Hazardous Substance

zinc oxide (as zinc)

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Pennsylvania - Workplace Hazard

Pennsylvania - Environmental Hazard

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the

HE280DC - WHITE ELASTOMERIC ROOF COATING

15. Regulatory Information - Continued

Canadian Regulatory Information - Continued

information required by the CPR. WHMIS Classification: D2A - Very Toxic

Ingredient(s) - Canadian Regulatory Information

silica, quartz

WHMIS - Ingredient Disclosure List


zinc oxide (as zinc)

WHMIS - Ingredient Disclosure List

WHMIS - Canada (Pictograms)



NFPA



HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 12/10/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

HENRY COMPANY