



SAFETY DATA SHEET

Issue Date 29-Nov-2015

Revision Date 31-Dec-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name Pro-Grade 586 Fibered Aluminum Roof Coating

Other means of identification

Product Code PG586

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Coatings Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY
999 N. Sepulveda Blvd., Suite 800
El Segundo, CA 90245-2716
Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



Appearance viscous

Physical state liquid

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating / lighting/ mixing / equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up
Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

24.67952% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

Chemical Name	CAS No	Weight-%
Solvent naphtha, petroleum, medium aliphatic *	64742-88-7	15 - 40

Asphalt *	8052-42-4	15 - 40
Aluminum *	7429-90-5	10 - 30
Perlite *	93763-70-3	5 - 10
Glass, oxide, chemicals *	65997-17-3	1 - 5
Benzene, 1,2,4-trimethyl- *	95-63-6	1 - 5
Solvent naphtha, petroleum, light aromatic *	64742-95-6	1 - 5

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

- General advice** Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
- Eye contact** Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
- Skin contact** Wash off immediately with plenty of water.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
- Ingestion** Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
- Self-protection of the first aider** Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	-	TWA: 500 ppm TWA: 2900 mg/m ³	-
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al
Perlite 93763-70-3	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Glass, oxide, chemicals 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable fraction	-	-
Benzene, 1,2,4-trimethyl- 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering Controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Solvent
Appearance	viscous	Odor threshold	No information available
Color	silver black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	> 150 °C / 302 °F	
Flash point	42 °C / 108 °F	Pensky-Martens Closed Cup (PMCC)
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	6	
Lower flammability limit:	1	
Vapor pressure	No information available	
Vapor density	3.6	
Relative density	1 - 1.1	
Water solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	>250 °C / 482 °F	
Decomposition temperature	No information available	
Kinematic viscosity	> 100 mm ² /s	@ 40 °C
Dynamic viscosity	No information available	
Explosive properties	Not an explosive	
Oxidizing properties	Not applicable	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Benzene, 1,2,4-trimethyl- 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt 8052-42-4	-	Group 2B	-	X
Glass, oxide, chemicals 65997-17-3	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)
 A2 - Suspected Human Carcinogen
 IARC (International Agency for Research on Cancer)
 Group 1 - Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 Not classifiable as a human carcinogen
 NTP (National Toxicology Program)
 Known - Known Carcinogen
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.
STOT - single exposure Target Organs. Respiratory system. Eyes. Skin. Central nervous system.
STOT - repeated exposure No information available.
Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system.
Target Organ Effects Eyes, Respiratory system, Skin, blood, Central nervous system, kidney.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5,252.00 mg/kg
ATEmix (dermal) 2,573.00 mg/kg
ATEmix (inhalation-dust/mist) 67.40 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

65.68642 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient
Asphalt 8052-42-4	6
Benzene, 1,2,4-trimethyl- 95-63-6	3.63

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	California Hazardous Waste Status
Aluminum 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

DOT Not regulated (If shipped in NON BULK packaging by ground transport)

TDG Not regulated (If shipped in NON BULK packaging by ground transport)

IATA

UN/ID no UN1999
 Proper shipping name Tars, liquid
 Hazard Class 3
 Packing Group III
 ERG Code 3L
 Special Provisions A3
 Description UN1999, Tars, liquid, 3, III

IMDG Non-regulated per 2.3.2.5
 UN/ID no UN1999
 Proper shipping name Tars, liquid
 Hazard Class 3
 Packing Group III
 EmS-No F-E, S-E
 Special Provisions 955
 Description UN1999, Tars, liquid, 3, III, (42°C c.c.)

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 IECSC Complies
 KECL Complies
 PICCS Complies
 AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Aluminum - 7429-90-5	1.0
Benzene, 1,2,4-trimethyl- - 95-63-6	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
 Chronic Health Hazard No
 Fire hazard Yes
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level

pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Cumene - 98-82-8	Carcinogen
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	X	-	-
Asphalt 8052-42-4	X	X	X
Aluminum 7429-90-5	X	X	X
Perlite 93763-70-3	X	X	X
Benzene, 1,2,4-trimethyl- 95-63-6	X	X	X
Cumene 98-82-8	X	X	X
Diethylbenzenes 25340-17-4	X	-	-
Quartz 14808-60-7	X	X	X
Water 7732-18-5	-	-	X
1,3,5-Trimethylbenzene 108-67-8	-	X	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

Issue Date 29-Nov-2015

Revision Date 31-Dec-2015

Revision Note
No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet