



Last Rev Date: 04/12/2012

### Physical Properties

<b>Appearance</b> Smooth gloss black	<b>Drying Time @ 50% R.H. 68°F (20°C)</b> 8 hrs set to touch	<b>Solids By Weight</b> 74% minimum
<b>Base</b> Refined asphalt	<b>Flash Point</b> 105° F (ASTM D-3278)	<b>Specific Gravity @ 77° F (25°C)</b> 0.93
<b>Brookfield Viscosity</b> 2000-4000 cPs	<b>Gloss</b> (60°) >80	<b>Weight Per Gallon</b> 7.6- 8.2 lbs (ASTM D-1475)
<b>Consistency @ 77° F</b> Brush, Spray	<b>Maximum VOC</b> 247 g/l	

### Description

**HE101 - NON-FIBERED FOUNDATION COATING** is a cold applied, non-fibrated, liquid asphalt in a solvent system ideal for dampproofing above and below grade exterior concrete and masonry walls and foundations that are thoroughly dry. NOT TO BE SOLD IN SOUTHERN CALIFORNIA.

### Usage

**HE101 - NON-FIBERED FOUNDATION COATING** is recommended for commercial or residential foundations.

### Coverage

1.5 to 2.0 gallons per 100 square feet. Do not over-apply.

### Surface Preparation

FOR EXTERIOR USE ONLY. Surface must be clean and dry, and free of moisture both on and beneath the surface. Remove rust and scale from metal by wire brushing. Carefully inspect entire area to be coated. Repair all cracks, breaks, tears and holes.

### Application

Stir coating thoroughly. Do not thin. Apply a single coat over the entire surface with a brush or heavy duty spray equipment.

### Precautions

In cold weather, store **HE101 - NON-FIBERED FOUNDATION COATING** in a warm room overnight before using. DO NOT APPLY IF THERE IS A THREAT OF RAIN WITHIN 24 HOURS. Avoid contact with coating after it is applied. Over-application, especially in cold weather, may cause sagging. Exposed coating tends to soften in warm weather. Do not heat container or store at temperatures greater than 110°F. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

### Cleanup

Remove coating from tools, etc., with paint thinner or mineral spirits. Clean hands with a waterless hand cleaner.

## Caution

**WARNING! COMBUSTIBLE!** Contains petroleum distillate. Keep away from heat and flame. CLOSE AIR INTAKES until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations. **DANGER! HARMFUL OR FATAL IF SWALLOWED!** If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. In case of accidental injection by power spray equipment, GET MEDICAL ATTENTION IMMEDIATELY!

**USE ONLY WITH ADEQUATE VENTILATION!** Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

**KEEP OUT OF REACH OF CHILDREN!**

**WARNING!** This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

**Employers** should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from the toll free number or website below.

## Product Sizes

5 GALLON (41.9 lb)

## Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**