

Termination Bar



Henry Termination Bar is an extruded aluminum bar that is designed for securing and sealing compression type flashing terminations. Termination Bar has pre-punched holes every 6" on center. Termination Bar features an extended top edge for ease of applying Henry Lap Sealant for Henry EPDM installations or Henry Single-Ply Sealant for Henry TPO installations. Termination Bar can be easily cut to any desired length. When installing, make sure that all corners of cut bar are rounded. Install Termination Bar using a threaded masonry fastener or masonry nail-in anchors.

Size

- 1" x 10' (25 mm x 3.05 m)

Typical Properties and Characteristics

Property	Results
Material	6036-T6 extruded aluminum
Dimensions	1" x 10' (25 mm x 3.05 m)
Packaging	50 pcs/carton
Weight	69 lbs (31 kg) carton

For more information, visit www.henry.com or for technical assistance call us at 800-486-1278. Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at www.henry.com or by emailing Henry Product Support at productsupport@henry.com or by calling 800-486-1278.

Henry and #1 Choice of Professionals are registered trademarks of Henry Company.

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.