

Physical Properties

Appearance black aggregate mix	Flammability Non-combustible	Specific Gravity @ 77° F (25°C) 2.3
Color Black	Flash Point 170° F.	Weight Per Gallon 11.1 - 11.5 lbs.
Drying Time @ 50% R.H. 68°F (20°C) Traffic immediately after compacting	Maximum VOC 60 g/l	

Description

HE304 - DRIVEWAY ASPHALT POTHOLE PATCH is a ready-to-use asphalt and aggregate compound for filling potholes and cracks in asphalt paved driveways, parking areas, and pathways. It is convenient, quick setting, and compacts to a smooth, long lasting patch.

Features:

- No special tools required
- Permanent repair
- No mixing necessary
- All weather - hot or cold, wet or dry

Coverage

Approximately 2 sq. ft. x 1 in. depth per 11 lb. container

Surface Preparation

FOR USE ON EXTERIOR ASPHALT SURFACES ONLY.

Material should be room temperature or higher just prior to use. DO NOT HEAT CONTAINER. Brush away any loose debris or standing water. Remove any weeds and kill roots with weed killer.

Application

DO NOT THIN. Remove lid and turn the pail upside down and shake until material releases. Spread with a trowel, rake or shovel and maintain approximately 1 1/2" above surface of repair area. Tamp down with trowel, shovel, or roll with wheels of car or truck. For holes more than 2" deep, apply in multiple layers, each no more than 2" thick, tamping each layer down completely before adding the next layer. For best appearance, cover with a piece of plywood prior to wheel rolling. Can take traffic immediately after compacting. Allow to cure for 3 weeks before sealing.

Precautions

When transporting this product, be sure the pail is secured to prevent pail from tumbling to prevent leakage.

Cleanup

Remove coating from tools, etc. with **Henry Scrubbers™ Hand & Tool Cleaning Towels** or kerosene, paint thinner or mineral spirits. Use care when handling solvents. Clean hands with **Henry Scrubbers™** or waterless hand cleaner.

Caution

WARNING! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F. **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations. **DANGER! HARMFUL OR FATAL IF SWALLOWED!** If swallowd, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **GET MEDICAL ATTENTION!**

USE ONLY WITH ADEQUATE VENTILATION! Avoid breathing of vapor. If you experience eye water, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

FOR EXTERIOR USE ONLY.

KEEP OUT OF REACH OF CHILDREN!

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

GALLON (12.75 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**