



TECHNICAL DATA SHEET  
**Tie-Back Cover**  
Pre-formed Plastic Detailing Cover

Physical property	Typical value	Test method
Color	Black	-
Impact Strength	@ 73° F (23° C) 4.0ft-lbs/in.	ASTM D256
Flexural Yield Strength	11,000 lbs. / in <sup>2</sup>	ASTM D790
Cavity Dimensions	8 in. D x 16 in. W (at base) (200mm x 400mm)	-

### Description

**Henry® Tie-Back Cover** is a durable pre-formed, high-impact resistant, thermoplastic cover designed to protect the waterproofing system integrity at soil retention tie-back systems. The **Henry Tie-Back Cover** is a robust detailing accessory and is an integral part of the **Henry® Blueskin PreSeal™** Waterproofing system.

### Features and benefits

- Fast and simple installation
- Provides a continuous waterproofing system across critical detail areas
- Chemically resistant
- Compatible with Henry waterproofing systems

### Usage

Designed for detailing soil retention tie-back systems in pre-applied waterproofing applications, **Henry Tie-Back Cover** can be installed for details on both horizontal and vertical waterproofing.

### Application

**Surface Preparation:** Fill voids in soil retention system prior to waterproofing membrane installation. Install **Henry Blueskin PreSeal** membrane around the tie-back head closely. Set the **Henry Tie-Back Cover** into **Henry 925 BES Sealant** or **Blueskin PreSeal Tape 50S** on the perimeter of the flange, covering the tie-back head. Mechanically attach **Henry Tie-Back Cover** 1" (25mm) from the exterior flange into the **Henry Blueskin PreSeal**. Fastener heads should be covered with **Henry 925 BES Sealant** prior to application of the **Blueskin PreSeal Tape 120V**.

Install a 1/8" (3.2mm) bead of **Henry 925 BES Sealant** at the edge of the **Henry Tie-Back Cover** and the **Blueskin PreSeal** membrane. Attach the **Blueskin PreSeal** to the **Henry Tie-Back Cover** a minimum of 6" (150mm) with the **Blueskin PreSeal Tape 120V** on all sides, covering the **Henry 925 BES Sealant**.

Refer to [www.henry.com](http://www.henry.com) for detailed application information.

### Product size/packaging

Cover Size 30 in. x 30 in. x 8 in. (762 mm x 762 mm x 200 mm)  
10 Covers/Box

### Storage

Shelf Life: Two years from date of manufacture.

**Henry® Tie Back Cover** should be stored dry and between, at 40 °F (4 °C) to 90 °F (32 °C).

## Henry® Tie-Back Cover

---

For more information, visit [www.henry.com](http://www.henry.com) or for technical assistance call us at 800-486-1278. For more information on the Henry® product warranty and liability disclaimer please visit [www.henry.com/warranty](http://www.henry.com/warranty). Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at [www.henry.com](http://www.henry.com) or by emailing Henry® Product Support at [productsupport@henry.com](mailto:productsupport@henry.com) or by calling 800-486-1278.

Henry and Blueskin are registered trademarks of Henry Company. PreSeal or Blueskin PreSeal are trademarks of Henry Company.

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry® Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.