

07560 Membrane Roofing/Acrylic Primers



1. PRODUCT NAME

ClearSeal A101
Surface Sealer & Conditioner

2. MANUFACTURER

NATIONAL COATINGS CORP.
1201 Calle Suerte
Camarillo, CA 93012
Phone: 800-423-9557
Fax: 800-294-3866
www.nationalcoatings.com
info@nationalcoatings.com

3. PRODUCT DESCRIPTION

ClearSeal A101 is a clear, flexible, water based sealer and conditioner for surfaces that have marginally adhered granules and fibers.

A101 is excellent for use over: Asphalt BUR, Mineral Cap Sheet, Modified Bitumen, Concrete, Transite, and other Porous Surfaces.

BENEFITS:

- *Seals & Conditions*
- *Provides Excellent Adhesion*
- *Water Based Technology*
- *Safe and Easy to Use*
- *Ultra Low VOC*

4. TECHNICAL DATA

See table below.

5. INSTALLATION

- May be applied by spray, brush, or roller.
- All surfaces must be clean, dry, and free of dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- Apply at temperatures above 50°F.
- Apply only when weather conditions will permit drying before rain, dew or freezing temperatures.
- Cool temperatures and high humidity retard cure.
- For application details see specific Installation Guide Specifications.

6. STORAGE

Store materials between 40°F and 100°F to prevent damage to products. Do not store at high temperatures or direct sunlight. Protect all materials from freezing during transit, handling, storage, and installation. Minimum one year shelf life if stored at 40°F-90°F.

7. AVAILABILITY AND COST

ClearSeal A101 may be purchased directly from National Coatings. For information call 800-423-9557.

8. WARRANTY

Various warranties are available for **ClearSeal A101** when used with specific AcryPly® Roofing Systems and AcryShield® Restoration Systems installed by approved applicators.

9. MAINTENANCE

Periodic maintenance of AcryPly Roofing Systems and AcryShield Restoration Systems containing **A101** ensures extended performance and reduces life-cycle costs.

10. TECHNICAL SERVICES

Additional information, product brochures, and installation guide specifications are available.

11. FILING SERVICES

Additional product information is available from National Coatings.

TECHNICAL DATA

Properties	Test Method	Average Value A101
Color		Milky white, dries clear
Theoretical Coverage		200 sq. ft/gal.
Solids by Volume (%)	Calculated by formula	24% (+/-1%)
Weight per Gallon (lbs.)		8.5
Clean-up		water
Drying Time (hrs.)		½ to 1*

*Drying time is dependent on temperature & humidity

This product is for industrial/commercial applications only. These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control.

