

Product Certification

Henry® Blueskin® Metal Clad® and Blueskin Metal Clad LT Self-Adhered Water Resistive Air Barrier

Blueskin Metal Clad and Blueskin Metal Clad LT are self-adhered burn and UV resistant air and vapor barriers comprised of a rubberized asphalt adhesive factory-applied to a composite facer of cross-laminated HDPE and aluminum foil, intended for use in above-grade wall assemblies. Henry manufacturing facilities implement full time quality control and are ISO certified. Henry products are tested to confirm compliance with the physical properties as stated on the product data sheet.

Blueskin Metal Clad and Blueskin Metal Clad LT meets following standards:

- ASTM E2357 - Assembly Air Leakage
- NFPA 285 - Complies in various wall assemblies
- Meets IBC 2018 – Section 1402.5, NFPA 285 exception #2 per ASTM E1354 and ASTM E84
- Declaration status: LBC Red List Free

Blueskin Metal Clad and Blueskin Metal Clad LT are chemically compatible with the following substrates: precast and cast-in place concrete, masonry, steel, aluminum, galvanized metal, exterior grade gypsum board, foil or coated-glass faced polyisocyanurate foam sheathing, OSB and plywood.

Blueskin Metal Clad and Blueskin Metal Clad LT are chemically compatible with the following commonly used Henry products:

- Air-Bloc® Liquid-Applied Air Barriers
- Air-Bloc LF®
- Aquatac™ Primer
- Blueskin Adhesive
- Blueskin Butyl Flash
- Blueskin LVC Adhesive
- Blueskin LVC Spray Primer
- Blueskin PE200HT
- Blueskin SA / Blueskin SA LT
- Blueskin TWF Thru-Wall Flashing
- Blueskin VP160
- Blueskin WP200
- Henry 925 BES Sealant

Blueskin Metal Clad does not contain lead, PBDE or PCBs, and has a VOC content of 0 g/L, max.

Refer to the product specific technical data sheet available at www.henry.com for further information or contact Henry Technical Support at 800-486-1278.