



**BLUESKIN PRESEAL 320
OR BLUESKIN PRESEAL 435**

HENRY 925 BES SEALANT

ANCHOR WITH SPACER TO ENSURE
PROPER FASTENER EMBEDMENT

HENRY 925 BES SEALANT

EXPANSION JOINT FOR GAPS UP
TO 2" (50MM) WIDE

SET EXPANSION JOINT INTO A BED
OF WET **HENRY 925 BES SEALANT**

**BLUESKIN PRESEAL 320
OR BLUESKIN PRESEAL 435**

COMPACTED EARTH, COMPACTED STONE
OR MUD SLAB (COMPACTED EARTH AND
COMPACTED STONE APPLICATIONS MUST
USE **BLUESKIN PRESEAL 435**)

SECTION VIEW
DECK TO DECK

NOTES:

1. DETAIL SHOWS HENRY PRE-APPLIED WATERPROOFING SYSTEM FOR APPLICATIONS USING HENRY **BLUESKIN PRESEAL 320** OR **BLUESKIN PRESEAL 435**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY.
2. HENRY **BLUESKIN PRESEAL 435** CAN BE INSTALLED DIRECTLY ONTO SHEET PILING. **BLUESKIN PRESEAL 320** REQUIRES A SMOOTH SURFACE SUCH AS PLYWOOD OR DRAINBOARD.
3. HENRY RECOMMENDS THE USE OF A DRAINBOARD IN NON-HYDROSTATIC CONDITIONS, OR AS A SUBSTRATE PREPARATION.
4. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.



MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

HENRY PRE-APPLIED WATERPROOFING SYSTEM

EXPANSION JOINT
DECK TO DECK
GAPS UP TO 2" (50MM) WIDE MAXIMUM

SCALE: N.T.S. 09-14-2022

BSPS-11B1