



**BLUESKIN WP200**  
(PRIMER NOT SHOWN FOR CLARITY - SEE DATA SHEET FOR RECOMMENDATIONS)

**HENRY DRAINAGE COMPOSITE**

**SYNKO-FLEX WATERSTOP, MIRASTOP BW, OR MIRASTOP NBW**  
(SEE NOTE #2)

**BLUESKIN WP200**  
(PRIMER NOT SHOWN FOR CLARITY - SEE DATA SHEET FOR RECOMMENDATIONS)

**HENRY 925 BES SEALANT**  
**HENRY 925 BES SEALANT**  
(EXTEND 3/4" (20MM) EACH SIDE)

**BLUESKIN PRESEAL 320 OR BLUESKIN PRESEAL 435**  
(COMPACTED EARTH OR COMPACTED STONE APPLICATIONS MUST USE **BLUESKIN PRESEAL 435**)

**NOTES:**

1. DETAIL SHOWS HENRY PRE-APPLIED WATERPROOFING SYSTEM FOR APPLICATIONS USING HENRY **BLUESKIN PRESEAL 320** OR **BLUESKIN PRESEAL 435**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY.
2. APPLICATIONS USING SWELLABLE WATERSTOPS: 3" (75MM) MINIMUM CONCRETE COVERAGE ON ALL SIDES.
3. HENRY RECOMMENDS THE USE OF A DRAINBOARD IN NON-HYDROSTATIC CONDITIONS, OR AS A SUBSTRATE PREPARATION.
4. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

**HENRY PRE-APPLIED WATERPROOFING SYSTEM**

**SLAB TO WALL TRANSITION**  
**BLUESKIN PRESEAL 320 OR BLUESKIN PRESEAL 435**  
**TRANSITION WITH BLUESKIN WP200 AT FOOTING**

SCALE: N.T.S. 09-14-2022

**BSPS-1C1A**

