



HENRY DRAINAGE
COMPOSITE

SYNKO-FLEX WATERSTOP,
MIRASTOP BW, OR
MIRASTOP NBW
(SEE NOTE #2)

MODIFIEDPLUS G100S/S OR
PROTECTION FABRIC GR08

HENRY CM100 2-PLY 120 MIL
REINFORCED WITH
POLYESTER FABRIC

HENRY 990-25 ELASTOMERIC
FLASHING SHEET
(SET FLASHING IN 60 MILS
OF HENRY CM100)

BLUESKIN PRESEAL 320
OR BLUESKIN PRESEAL 435
(COMPACTED EARTH OR
COMPACTED STONE
APPLICATIONS MUST USE
BLUESKIN PRESEAL 435)

4" (100MM)

6" (150MM)

NOTES:

1. DETAIL SHOWS HENRY PRE-APPLIED WATERPROOFING SYSTEM FOR APPLICATIONS USING HENRY **BLUESKIN PRESEAL 320** OR **BLUESKIN PRESEAL 435**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY.
2. APPLICATIONS USING SWELLABLE WATERSTOPS: 3" (75MM) MINIMUM CONCRETE COVERAGE ON ALL SIDES.
3. HENRY RECOMMENDS THE USE OF A DRAINBOARD IN NON-HYDROSTATIC CONDITIONS, OR AS A SUBSTRATE PREPARATION.
4. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

HENRY PRE-APPLIED WATERPROOFING SYSTEM

SLAB TO WALL TRANSITION
BLUESKIN PRESEAL 320 OR BLUESKIN PRESEAL 435
TRANSITION WITH HENRY CM100 AT FOOTING

SCALE: N.T.S.

09-14-2022

BSPS-1C2

