



- HENRY DRAINBOARD (SEE NOTE #3)
- BLUESKIN PRESEAL 320
OR BLUESKIN PRESEAL 435 (SEE NOTE #2)
- NON SHRINK GROUT (BY OTHERS)
- SEAL PIPE WITH **BLUESKIN PRESEAL TAPE 120V**
- MIRASTOP BW OR MIRASTOP NBW**
(3" (75MM) MINIMUM CONCRETE
COVERAGE ON ALL SIDES)
- PVC OR METAL PIPE
- HENRY 925 BES SEALANT**
(EXTEND 3/4" (20MM) EACH SIDE)
- MECHANICAL SEAL BY OTHERS
(WATER TIGHT INTEGRITY OF
SLEEVE BY OTHERS)
- SOIL RETENTION SYSTEM
(DO NOT INSTALL **BLUESKIN
PRESEAL 320** DIRECTLY ONTO
SHEET PILING - PREPARE
SUBSTRATE WITH A SMOOTH
SURFACE SUCH AS PLYWOOD OR
DRAINBOARD)

NOTES:

1. DETAIL SHOWS HENRY PRE-APPLIED WATERPROOFING SYSTEM FOR APPLICATIONS USING HENRY **BLUESKIN PRESEAL 320** OR **BLUESKIN PRESEAL 435**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY.
2. HENRY **BLUESKIN PRESEAL 435** CAN BE INSTALLED DIRECTLY ONTO SHEET PILING. **BLUESKIN PRESEAL 320** REQUIRES A SMOOTH SURFACE SUCH AS PLYWOOD OR DRAINBOARD.
3. HENRY RECOMMENDS THE USE OF A DRAINBOARD IN NON-HYDROSTATIC CONDITIONS, OR AS A SUBSTRATE PREPARATION.
4. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

HENRY PRE-APPLIED WATERPROOFING SYSTEM

WALL PENETRATION

**BLUESKIN PRESEAL 320 OR BLUESKIN PRESEAL 435
WALL PENETRATION - SINGLE PIPE SLEEVE**

SCALE: N.T.S.

09-14-2022

BSPS-6B1

