



**NOTES:**

1. DETAIL SHOWS HENRY **DUNDEQ** SYSTEM FULL SEED AND LOCK TRAFFIC COATING. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
2. HENRY **DUNDEQ** SYSTEM STANDARD PRIMERS: **HENRY LV PRIMER** AND **HENRY LVXL PRIMER**.
3. OTHER RECOMMENDED PRIMERS INCLUDE: **HENRY ST PRIMER** AND AGGREGATE, **HENRY STXL PRIMER** AND AGGREGATE, **PUMADEQ PRIMER 20** AND AGGREGATE OR **HENRY GC EPOXY PRIMER**. REFER TO THE **DUNDEQ** SYSTEM SUBSTRATE PRIMER GUIDELINES TECH-TALK BULLETIN FOR APPLICATION RECOMMENDATIONS.
4. FULLY BROADCAST, TO REJECTION, DRY SILICA SAND INTO WET WEAR COAT (SIEVE SIZE: #20-50, #12 SILICA OR NJ0-NJ00).
5. DO NOT INSTALL **DUNDEQ** SYSTEM BEYOND PRIMED SURFACES.
6. EXPANSION JOINT MANUFACTURED AND INSTALLED BY OTHERS AS SPECIFIED. CONTACT HENRY FOR PROJECT SPECIFIC COORDINATION OF TRAFFIC COATING WITH EXPANSION JOINT.
7. REFER TO **DUNDEQ** SYSTEM GUIDE SPECIFICATION AND **DUNDEQ** SYSTEM DETAILS FOR RECOMMENDED INSTALLATION PROCEDURES.

**Henry**<sup>®</sup>

999 N. Pacific Coast Highway, Suite 800  
El Segundo, CA 90245  
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

**DUNDEQ SYSTEM - PEDESTRIAN/VEHICULAR TRAFFIC COATING**

**EXPANSION JOINT**

**FULL SEED AND LOCK  
PEDESTRIAN AND VEHICULAR TRAFFIC COATINGS**

SCALE: N.T.S.

04-10-2020

**DUNDEQ-EJ3**