



A step 2 component of the Henry® 1-2-3 Moisture Control System™



FortiFlash® Fusion™ Flashing Membrane

Consistent and Cost-Effective Performance

FortiFlash® Fusion™ Waterproof Flashing Membrane is our next generation flashing that delivers exceptional quality, performance and value allowing installers to meet tight schedules and even tighter budgets. Fortiflash Fusion features a new butyl based adhesive technology that provides reliability in high temperatures up to 180 °F and protects against moisture intrusion so you can install with confidence even in the the most demanding environments.

FortiFlash Fusion Waterproof Flashing Membrane provides a strong, self-sealing barrier that protects windows, doors and through-wall penetrations and is designed to withstand the rigors of the jobsite and the elements. When used as part of the Henry® 1-2-3 Moisture Control System™ it is backed by an industry-leading 15-year material PLUS labor warranty for product defects.

Features and benefits



Durable butyl-based core and facer protects against delamination and tears



Can be installed at temperatures as low as 30 °F (-1 °C), and as high as 120 °F (-49 °C) so projects stay on track no matter what the condition.



Compatible with Moistop® Sealant



Self-seals around nails and fasteners for lasting watertightness



AAMA 711 compliant



For additional product specifications and warranty information scan here.

Building Confidence®



Steps 2 & 3 of the Henry® 1-2-3 Moisture Control System™ for 15 years of warranty coverage



Henry® Residential & Light Commercial Flashing & Sealants Selection Chart

	Self Adhered					Liquid Applied			Mechanically Fastened		Sealants	
	Blueskin® ZeroFlash™	FortiFlex® Butyl	FortiFlash® Butyl	FortiFlash® Fusion™	Moistop E-Z Seal®	FortiFlash®	Air-Bloc LF® Liquid-Applied Flashing	Moistop PF®	Moistop® Sealant	Henry® 212 All Purpose Crystal Clear Sealant		
Vapor Permeable							•					
Vapor Impermeable	•	•	•	•	•	•		•	•	•		•
AMAA 711 Compliant (self adhered & mechanically fastened)	•	•	•	•	•	•	n/a	•	•	•		n/a
AMAA 714 Compliant (liquid applied)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a		n/a
Minimum Application Temperature	0 °F	10 °F	25 °F	30 °F	40 °F	40 °F	20 °F	n/a	40 °F	40 °F		32 °F
Service Temperature	-40 ° to 180 °F	-40 ° to 200 °F	-40 ° to 250 °F	-40 ° to 180 °F	-40 ° to 176 °F	-40 ° to 149 °F	-40 ° to +200 °F	n/a	-40 ° to 180 °F	-40 ° to 180 °F		-40 ° to 180 °F
Low VOC	n/a	n/a	n/a	n/a	n/a	n/a	•	n/a	n/a	n/a		n/a
Nail Sealability	•	•	•	•	•	•	•	n/a	n/a	n/a		•
Red List Free	•	•	•	•	•	•	•	•	•	•		•
Henry 1-2-3 Moisture Control System	•	•	•	•	•	•	•	•	•	•		•

VOC regulations do not apply to articles such as sheet applied membranes and flashings. VOCs are only measured in certain liquid products.



Nail Sealability:

Meet ASTM D1970 and AAMA 711 for sealing around fasteners, eliminating water penetration even after the exterior facade is installed.

Consult updated Technical Data Sheet for most recent information

Henry, Blueskin, FortiFlex, FortiFlash, Moistop, and Air-Bloc are registered trademarks of the Henry Company.

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.

productsupport@henry.com | 1-800-486-1278

www.henry.com

Building Envelope Systems®
Roofing | Air Barrier | Waterproofing

© 2023 Henry Company All rights reserved.
Printed in U.S.A. 100.3US.E641 (08/23)