

## Warranty program

# Henry® Asphalt Roof Emulsion Coating System

Henry Asphalt Roof Emulsion Coating Systems extend the life cycle of your roof resulting in a cost-effective alternative to a full replacement.

### Warranty options from Henry®

- Choose your desired level of warranty protection to meet your needs: Material Plus or Gold Seal.
- Both options can be available when installation is in compliance with the information below.

### Material Plus Warranty

This warranty option provides material and labor coverage at no charge during the applicable warranty term to repair the affected roof area when product manufacturing defects have been determined. Product(s) must be installed by a Material Plus or Gold Seal Authorized Contractor.

### Gold Seal Warranty

This warranty option provides material and labor to repair the affected area when product defects or workmanship installation deficiencies have been determined. Product(s) must be installed by a Gold Seal Authorized Contractor.

## Warranty installation options

10-year Asphalt Emulsion roof coating system					
		Granulated Cap Sheet	Smooth Cap sheet/BUR (non-aggregate)	Warranty Cost	
				Materials Plus	Gold Seal
<b>FC</b>	Pro-Grade® 197	40 mils DFT min. 5 gal/sq	32 mils DFT min. 4 gal/sq	No cost	\$0.06/sq.ft. \$900 min
<b>BC</b>	AcryShield® Base Coat 400*, 505	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
<b>TC</b>	AcryShield® Top Coat 510, 550 HT or 610	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
	Total (min. thickness)	66 mils DFT min. 8 gal/sq	58 mils DFT min. 7 gal/sq		

15-year Asphalt Emulsion roof coating system**					
		Granulated Cap Sheet	Smooth Cap sheet/BUR (non-aggregate)	Warranty Cost	
				Materials Plus	Gold Seal
<b>FC</b>	Pro-Grade® 197	32 mils DFT min. 4 gal/sq	24 mils DFT min. 3 gal/sq	No cost	\$0.08/sq.ft. \$1200 min
<b>R</b>	Henry® 195 Polyester Fabric	Reinforcing layer	Reinforcing layer		
<b>FC</b>	Pro-Grade® 197	32 mils DFT min. 4 gal/sq	24 mils DFT min. 3 gal/sq		
<b>BC</b>	AcryShield® Base Coat 400*	17 mils DFT min. 2.0 gal/sq	17 mils DFT min. 2.0 gal/sq		
<b>TC</b>	AcryShield® Top Coat 510, 550 HT or 610	17 mils DFT min. 2.0 gal/sq	17 mils DFT min. 2.0 gal/sq		
	Total (min. thickness)	98 mils DFT min. 12 gal/sq	82 mils DFT min. 10 gal/sq		

**FC** Foundation coat    **BC** Base coat    **TC** Top coat    **R** Reinforcing layer

**NOTES:**

\* AcryShield 400 can be used as a top coat in certain assemblies/applications

\*\* Total thickness to be must be achieved but you must give consideration to temperature and humidity levels during the time of application for curing and application coats. Will require multiple coats

DFT = Dry Film Thickness (minimum requirement).

Product coverage rates represent minimum application requirement. Coverage rates are theoretical and do not take into account material loss due to spraying, surface texture, waste, etc. For previously coated roof membranes, the product coverage rates indicated in the charts above are applicable.

**Ancillary components for all warranted assemblies**

Application	Product name	Product description	Coverage rate
MB/BUR fasteners/defects	S Henry® 289 White Roofing Sealant	Roofing sealant	Varies by application
	S Seal-Tek Micro Fibers	Fibered roofing sealant	See application guidelines for mixing instructions
MB/BUR cap sheet	S Fully Reinforced System Not Required	n/a	n/a

**S** Sealant

**Material Plus Warranty Process**

- Step 1: Complete Authorized Contractor Application for a Henry® Material Plus Warranty and submit to [warranty@henry.com](mailto:warranty@henry.com).
- Step 2: Complete Henry® Extended Warranty Application by clicking on the following link: <http://us.henry.com/warranty>.
- Step 3: Complete the project following the appropriate AcryShield® Guide Specification.
- Step 4: Warranty typically issued within 10 business days upon completion of warranty application and project.

**Gold Seal Warranty Process**

- Step 1: Complete Authorized Contractor Application for a Henry® Gold Seal Warranty and submit to [warranty@henry.com](mailto:warranty@henry.com).
- Step 2: Complete Henry® Extended Warranty Application by clicking on the following link: <http://us.henry.com/warranty>.
- Step 3: Complete the project following the appropriate AcryShield® Guide Specification.
- Step 4: Final inspection is completed by an authorized Henry® Representative and submitted to [warranty@henry.com](mailto:warranty@henry.com).
- Step 5: Warranty typically issued within 10 business days upon completion of warranty application, project and final inspection.

**Call 1-800-486-1278 or email [warranty@henry.com](mailto:warranty@henry.com) for more warranty information.**