

Warranty program

Henry® Acrylic Roof Restoration Systems

Henry Acrylic Roof Coating Systems extend the life cycle of your roof resulting in a cost-effective alternative to a full replacement.

Warranty options from Henry®

- Choose your desired level of warranty protection to meet your needs: Material Plus or Gold Seal.
- Both options can be available when installation is in compliance with the information below.

Material Plus Warranty

This warranty option provides material and labor coverage at no charge during the applicable warranty term to repair the affected roof area when product manufacturing defects have been determined. Product(s) must be installed by a Material Plus or Gold Seal Authorized Contractor.

Gold Seal Warranty

This warranty option provides material and labor to repair the affected area when product defects or workmanship installation deficiencies have been determined. Product(s) must be installed by a Gold Seal Authorized Contractor.

Acrylic Restoration System Warranty installation options

10-year Acrylic Restoration Warranty								
		Granulated Cap Sheet	Smooth Cap/BUR (non-aggregate)	Single Ply (TPO, PVC, EPDM)	Metal	Aged or 1" new PremiR+ EVO SPF	Warranty Cost	
							Material Plus	Gold Seal
PC		As Required	As Required	As Required	As Required	As Required	No cost	0.06/sq. ft \$900 min.
BC	AcryShield® Base Coat 400, 505 or 605; 501 for SPF applications; or Pro-Grade 280 Acrylic**	15 mils DFT min. 1.75 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
TC	AcryShield Top Coat 400, 510, 550 HT and 610; or Pro-Grade 280 Acrylic	17 mils DFT min. 2 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
	Total (min. thickness)	32 mils DFT min. 3.75 gal/sq	26 mils DFT min 3 gal/sq	26 mils DFT min 3 gal/sq	26 mils DFT min 3 gal/sq	26 mils DFT min 3 gal/sq		

15-year Acrylic Restoration Warranty								
		Granulated Cap Sheet	Smooth Cap/BUR (non-aggregate)	Single Ply (TPO,PVC, EPDM)	Metal	Aged or 1.5" new PremiR+ EVO SPF	Warranty Cost	
							Material Plus	Gold Seal
PC		As Required	As Required	As Required	As Required	As Required	No cost	0.08/sq. ft \$1200 min.
BC	AcryShield Base Coat 400, 500 or 605; 501 for SPF applications; or Pro-Grade 280 Acrylic**	17 mils DFT min. 2 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
TC	AcryShield Top Coat 400, 510, 550 HT and 610; or Pro-Grade 280 Acrylic	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq		
	Total (min. thickness)	34 mils DFT min 4 gal/sq	30 mils DFT min. 3.5 gal/sq	30 mils DFT min. 3.5 gal/sq	30 mils DFT min. 3.5 gal/sq	30 mils DFT min. 3.5 gal/sq		

20-year Acrylic Restoration Warranty*								
		Granulated Cap Sheet	Smooth Cap/BUR (non-aggregate)	Single Ply (TPO,PVC, EPDM)	Metal	Aged or 1.5" new PremiR+ EVO SPF	Warranty Cost	
							Material Plus	Gold Seal
PC		As Required	As Required	As Required	As Required	As Required	No cost	0.10/sq. ft \$1500 min.
BC	AcryShield Base Coat 400, 505 or 605; 501 for SPF applications; or Pro-Grade 280 Acrylic**	17 mils DFT min. 2 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
TC1	AcryShield Top Coat 400, 510, 550 HT and 610; or Pro-Grade 280 Acrylic	17 mils DFT min. 2 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq	13 mils DFT min. 1.5 gal/sq		
TC2	AcryShield Top Coat 510, 550 HT, 610; or Pro-Grade 280 Acrylic	13 mils DFT min. 1.5 gal/sq	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq	17 mils DFT min. 2 gal/sq		
Total (min. thickness)		47 mils DFT min. 5.5 gal/sq	43 mils DFT min. 5 gal/sq	43 mils DFT min. 5 gal/sq	43 mils DFT min. 5 gal/sq	43 mils DFT min. 5 gal/sq		

PC Primer coat **BC** Base coat **TC1** Top coat 1 **TC2** Top coat 2

NOTES:
 * Most likely will require 3 coats
 ** When using Pro-Grade 280, Pro-Grade 294 can be used as a base coat; excluding SPF and single ply applications. Follow the appropriate Pro-Grade 280 Guide Specification.
 For cold storage or cryogenic structures, please contact your Henry Technical Representative.

DFT = Dry Film Thickness (minimum requirement).
 Product coverage rates represent minimum application requirement. Coverage rates are theoretical and do not take into account material loss due to spraying, surface texture, waste, etc. For previously coated roof membranes, the product coverage rates indicated in the charts above are applicable.

Material Plus Warranty Process

- Step 1: Complete Authorized Contractor Application for a Henry® Material Plus Warranty and submit to warranty@henry.com.
- Step 2: Complete Henry® Extended Warranty Application by clicking on the following link: <http://us.henry.com/warranty>.
- Step 3: Complete the project following the appropriate AcryShield® Guide Specification.
- Step 4: Warranty typically issued within 10 business days upon completion of warranty application and project.

Gold Seal Warranty Process

- Step 1: Complete Authorized Contractor Application for a Henry® Gold Seal Warranty and submit to warranty@henry.com.
- Step 2: Complete Henry® Extended Warranty Application by clicking on the following link: <http://us.henry.com/warranty>.
- Step 3: Complete the project following the appropriate AcryShield® Guide Specification.
- Step 4: Final inspection is completed by an authorized Henry® Representative and submitted to warranty@henry.com.
- Step 5: Warranty typically issued within 10 business days upon completion of warranty application, project and final inspection.

When using Pro-Grade 280, Pro-Grade 294 or AcryShield follow the appropriate Guide Specification and Application Guide available on Henry.com.

Call 1-800-486-1278 or email warranty@henry.com for more warranty information.



Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.